Product Family

NIT'LITE® RIGGER

Rubber soled safety rigger boot with 200J toe cap and anti-puncture steel midsole

Product Numbers & Ordering Information

	Product Numbers	Details
	6213953-38/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 38
	6213953-39/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 39
	6213953-40/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 40

	6213953-41/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 41
	6213953-42/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 42
	6213953-43/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 43
	6213953-44/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 44
	6213953-45/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 45
	6213953-46/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 46
	6213953-47/7	**BACOU NTL RIGGER S3 HRO SRC** Full grain natural tan leather rigger boot with pull on lugs. Complies with EN ISO 20345:2007 S3 HRO SRC standard. Size 47

Key Features

Safety rigger boot with 200J toe cap and anti-puncture steel midsole. nitrile outsole

Overview

Recommended Industries/Use

- Chemical
- Welding

Hazards

- Chemical
- Cut / Puncture
- Extreme Environment
- Impact
- Slip
- Splash

Regulations

- - - European Directive: 89/686/EEC - EC PPE Category II - Standard: EN ISO 20345:2007 - Marking : S3 HRO SRC Quality Assurance: ISO 9001:2008

Historical Brand

BACOU

Specifications

Upper	Full grain water resistant leather
Lining	None
Outsole	Vulcanized nitrile
Heat resistant outsole	Resistant to heat by contact up to 300°C
Toecap	Metallic 200J
Anti-puncture midsole	Stainless steel
Insole	Perforated
Size range	EU 38 - 47 UK 5 - 12

Instruction notice provided with product. Life Cycle: If the footwear is supplied with a part of, or the whole sole unit made of polyurethane: We advise that the footwear should be

Training & Proper Use

used in the limit of 3 years following the manufacturing date, which figures on the footwear. After this time limit, certain factors such as : exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE. If the footwear is supplied with a sole unit made from a material other than polyurethane: We advise that the footwear should be used in the limit of 5 years following the manufacturing date, which figures on the footwear. Storage: All of these time limits indicated, concern only new footwear in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels. Cleaning: - After use leave your footwear to dry in an aired place away from heat. - Remove any excess dust or dirt with a brush. - Remove any marks using a damp cloth and soap if necessary. - Finally polish any grain or pigmented leathers using a commercially available shoe care product.

Technical Support

http://www.sperianprotection.eu/sperian/contact-us

© Honeywell International Inc.