







**Product Family**  
**Fenzy X-Pro SCBA (AS/NZS)**

Self Contained Breathing Apparatus specially developed for firefighting. Its unique design offers comfort and high performance with the new "Extreme Comfort" harness, an ultra-light back plate adjustable to every morphology and a foldable foot guaranteeing a complete protection of the high pressure system.

**Honeywell**

**Product Numbers & Ordering Information**

Product Numbers	Details
 1823382	<b>Fenzy X-Pro SCBA - AS/NZS Standard</b> Includes size M full face mask "Opti-Pro" with silicone headstraps and "Fenzy SX-Pro" First Breath Activation demand valve, without cylinder
 1715029	<b>Replacement Mask</b> OptiPro Replacement mask for Fenzy Xpro
 107573	<b>200 Bar Cylinder</b> 9 Litre, 200 Bar Cylinder with Valve. Aluminium Hoop Wrap
 118245	<b>300 Bar Cylinder</b> 6.9 Litre, 300 Bar Cylinder with Valve. Carbon Fibre

**Overview**

**Key Features**

- Resistant to hostile environments : extreme temperatures, chemical products
- Integrated HP and MP hoses
- Fenzy Quick-Fix system allowing to replace cylinder quickly and easily
- Multiple anchoring rings for accessories and fast tightening straps
- Fenzy Opti-Pro full face mask with full panoramic vision without optical distortion
- Fenzy SX-Pro first breath demand valve
- New "Extreme Comfort" harness
- Ultra-light back plate, adjustable to every morphology for an optimum comfort

## Fenzy X-Pro SCBA (AS NZS)

- Movable and foldable foot guaranteeing a complete protection of the high pressure system

### Recommended Industries/Use

- Chemical
- Fire Protection
- Government
- Law Enforcement
- Military
- Mining
- Oil and Gas

### Hazards

- Airborne Particulates
- Biohazard
- Chemical
- Confined Space
- Contamination
- Extreme Environment
- Fire
- Gas, Vapors, Smoke

### Regulations

- AS/NZS 1716
- ISO 9001
- Bureau Veritas for Marine use (SOLAS, MSC and MED)

### Historical Brand

Fenzy

## Specifications

### Homologations

- AS/NZS 1716, ISO 9001, Bureau Veritas for Marine use (SOLAS, MSC and MED)

### Total weight of the complete set without cylinder

- 3,9 kg

### Harness

- Thermo-compressed comfort cushions on the shoulder and belt straps.

### Back-plate

- Anti-static polymeric resin

### Outlet pressure of the HP reducer

- 7 bars

### Pressure

- 200 or 300

### Outlet pressure of the HP reducer

- 7 bars

### Power of the pressure gauge whistle

- > 95 DbA

## Literature & Documents

Fenzy XPRO AUSNZ

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Respiratory\\_Protection/Self\\_Contained\\_Breathing\\_Apparatus\\_\(SCBA\)/4294998859/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/Self_Contained_Breathing_Apparatus_(SCBA)/4294998859/1033.aspx)

## Training & Proper Use

Including User's Manual

## Technical Support

### Australia/New Zealand

Ph Aus: 1300 139 166

Ph NZ: 0800 322 200

Email: [hlshspamarketing@Honeywell.com](mailto:hlshspamarketing@Honeywell.com)

### RELATED PRODUCTS

