



Produktfamilj

Miller ME83 Manyard Shock-Absorbing Lanyards (EUR)

Shock absorbing Lanyard - complete with 1 screwgate karabiner (ML00) and Automatic karabiner.

Miller Logo

Product Numbers &



1005326

Stretchable Shock-Absorbing Webbing

Complete 1,5m with 1 galvanised connector and 1 snap hook 22mm



1005327

Stretchable Shock-Absorbing Webbing

Complete 2m with 1 galvanised connector and 1 snap hook 22mm

Översikt

Viktigaste egenskaperna

Features :

- A unique stretchable design.
- A safety clip that straps on to the harness to hold the Manyard when not in use.
- Special woven shock-absorbing inner core.
- Heavy tubular outer jacket.
- Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service.
- Reliable visual inspection: the integral red core becomes visible if the outer jacket is damaged or worn.
- The hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

Benefits : Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or gantries. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

Rekommenderade branscher/rekommenderat användningsområde

- Byggindustri

Risker

Föreskrifter Föreskrifter

- EN 355 - Shock absorbers

Garantiinformation

Our state of the art equipment provides the critical tool for worker protection, combining mobility with unsurpassed comfort.

At our ISO 9001 certified manufacturing facilities in Europe, we ensure that every Miller product is made in accordance with the standards and meets your exacting requirements.

Trycksaker & dokument

90004208 lanyard EN 354, 355 (EUR)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards/41642/1033.aspx

Instruction manual

Teknisk support

Miller Techniserv

Phone: +49 (0) 9281/8302-205

Email: techniservnorth.hsp@honeywell.com