









**Product Family**  
**Miller TurboLite Personal Fall Limiters**














Never need a shock-absorbing lanyard AGAIN with the 6-ft or 9-ft lightweight personal fall limiters rated for a 400-lb worker!



**Product Numbers & Ordering Information**

Product Numbers	Details
 MFL-1/6FT	<b>6-ft TurboLite</b> Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook
 MFL-10/6FT	<b>6-ft TurboLite</b> Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Rebar Hook
 MFL-10-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Rebar Hook
 MFL-11/6FT	<b>6-ft TurboLite</b> Unit Connector: Aluminum Twist-Lock Carabiner; Lanyard End Connector: Aluminum Locking Snap Hook
 MFL-12/6FT	<b>6-ft TurboLite</b> Unit Connector: Aluminum Twist-Lock Carabiner; Lanyard End Connector: Aluminum Locking Rebar Hook
 MFL-1-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook

Miller TurboLite PFLs

	MFL-2/6FT	<b>6-ft TurboLite</b> Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Rebar Hook
	MFL-2-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Steel Twist-Lock Carabiner; Lanyard End Connector: Locking Rebar Hook
	MFL-3/6FT	<b>6-ft TurboLite</b> Unit Connector: None; Lanyard End Connector: Locking Snap Hook
	MFL-3-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: None; Lanyard End Connector: Locking Snap Hook
	MFL-4/6FT	<b>6-ft TurboLite</b> Unit Connector: None; Lanyard End Connector: Locking Rebar Hook
	MFL-4-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: None; Lanyard End Connector: Locking Rebar Hhook
	MFL-6/6FT	<b>6-ft TurboLite</b> Unit Connector: None; Lanyard End Connector: Locking Swivel Rebar Hook
	MFL-8/6FT	<b>6-ft TurboLite</b> Unit Connector: D-Ring Swivel Hook; Lanyard End Connector: Locking Rebar Hook
	MFL-9/6FT	<b>6-ft TurboLite</b> Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Snap Hook
	MFL-9-Z7/6FT	<b>6-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Locking Snap Hook; Lanyard End Connector: Locking Snap Hook
	MFL-1/9FT	<b>9-ft TurboLite</b> Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Snap Hook
	MFL-1-Z7/9FT	<b>9-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Snap Hook
	MFL-2/9FT	<b>9-ft TurboLite</b> Unit Connector: Steel Carabiner; Lanyard End Connector: Steel Rebar Hook

## Miller TurboLite PFLs

	MFL-9-Z7/9FT	<b>9-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Steel Snap Hook; Lanyard End Connector: Steel Snap Hook
	MFL-11/9FT	<b>9-ft TurboLite</b> Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Snap Hook
	MFL-11-Z7/9FT	<b>9-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Snap Hook
	MFL-12/9FT	<b>9-ft TurboLite</b> Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Rebar Hook
	MFL-12-Z7/9FT	<b>9-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Aluminum Carabiner; Lanyard End Connector: Aluminum Rebar Hook
	MFL-14-Z7/9FT	<b>9-ft TurboLite; 3,600 lb. Gate</b> Unit Connector: Aluminum Snap Hook; Lanyard End Connector: Aluminum Snap Hook

## Overview

### Key Features

Cost-effective, compact and lightweight, Miller TurboLite Personal Fall Limiters make the need for shock-absorbing lanyards obsolete.

- Reduces fall clearance requirements
- Available in 6-ft and 9-ft lengths to meet the needs of a wide variety of applications
- Extremely compact and lightweight, comparable to a shock-absorbing lanyard
- Attaches directly to the back D-ring of a harness for increased mobility
- High-impact resistant nylon housing and abrasion-resistant webbing provide long service life
- Integral swivel prevents lifeline from twisting
- Rated for up to a 400 lb. (181.4 kg) worker
- Twin models available for 100% tie-off
- Meets requirements of OSHA, ANSI Z359.14 Class A & B and CSA Z259.2.2.

### Miller 6-foot TurboLite PFL

- Ideal replacement for a 6-ft. shock-absorbing lanyard
- Ultra compact and lightweight

### Miller 9-foot TurboLite PFL

- Provides 9-ft. of working length, an ideal solution for scaffolding and order picker applications

### Recommended Industries/Use

- Construction
- Oil and Gas

### Hazards

- Confined Space
- Fall from height

## Regulations

- Meets all applicable OSHA, ANSI and CSA standards

## Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

## Literature & Documents

### TurboLite-TwinTurbo-brochure - US

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters/Self-Retracting\\_Lifelines/4294976298/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294976298/1033.aspx)

View Miller TurboLite/Twin Turbo Family Brochure

### SP408 TurboLite Series Spec Sheet - US

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters/Self-Retracting\\_Lifelines/16181/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/16181/1033.aspx)

SP408 6-ft Miller TurboLite Series Spec Sheet

### SP482 9-ft TurboLite spec - US

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters/Self-Retracting\\_Lifelines/4294976315/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294976315/1033.aspx)

SP482 9-ft Miller TurboLite Series Spec Sheet

## Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

## Additional Information

800/873-5242 or email: [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com)

## Technical Support

Contact Honeywell Technical Service at 800/873-5242 or email: [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com)

## RELATED PRODUCTS