



Miller Turbo T-BAK PFL

Product Family
Miller Turbo T-BAK™ Personal Fall Limiter

Tie-back safely with a retractable! The Miller Turbo T-BAK is a Tie-Back Personal Fall Limiter (PFL) designed to tie-back anywhere along the lifeline. For 100% tie-off fall protection,

Miller Logo

Product Numbers & Ordering Information

	Product Numbers	Details
	MFLT-1/7.5FT	Miller Turbo T-BAK Tie-Back Personal Fall Limiter Turbo T-BAK without unit connector
	MFLT-2/7.5FT	Miller Turbo T-BAK Tie-Back Personal Fall Limiter Turbo T-BAK with a 17D-1 steel twist-lock carabiner
	MFLT-3/7.5FT	Miller Turbo T-BAK Tie-Back Personal Fall Limiter Turbo T-BAK with a 17D-2 lightweight, aluminum twist-lock carabiner
	MFLTB-1/7.5FT	Miller Twin Turbo T-BAK D-Ring Connector System Twin Turbo D-Ring Connector with two MFLT-1/7.5FT Turbo T-BAK units

Overview

Key Features

- 7.5-ft. (2.3m) Working Capacity
- User-Rated to 400-lbs. (181kg) Capacity
- Cost-effective alternative to tie-back shock-absorbing lanyards.
- All-in-one, self-retracting lifeline/anchorage connector design reduces equipment required on the job site.
- Designed for anchoring below a user's harness back D-ring for greater safety.
- Integrated shock absorber especially designed for tie-back applications with load indicator device.
- Meets all applicable OSHA, ANSI, CSA and CE standards, including the ANSI Z359.1 requirement that states only 24-inches (.62m) or less of lifeline extends out of the housing when the unit is fully retracted.
- The new patent-pending **Miller Twin Turbo™ D-Ring Connector** easily adapts two Miller Turbo T-BAK PFLs for continuous 100% tie-off fall protection.

Recommended Industries/Use

- Other
- Construction
- Manufacturing
- Oil and Gas
- Utilities

Hazards

- Fall from height

Regulations

- Meets applicable OSHA, ANSI, CSA and CE standards, including ANSI Z359.1

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Specification Sheets

- For a full engineering specification sheet, go to Literature & Documents

Working Capacity

- 7.5-ft. (2.3m)

User-Rated Capacity

- 400-lbs. (181kg)

Housing

- High Impact Nylon

Literature & Documents

Miller Turbo T-BAK brochure - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/40026/1033.aspx

Product Brochure

SP445_Turbo T-BAK_US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/42918/1033.aspx

SP445 Turbo T-BAK Specification Sheet

Miller Turbo T-BAK FAQ - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/40027/1033.aspx

Frequently Asked Questions

Miller Turbo T-BAK Instruction Manual - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/40028/1033.aspx

Instruction Manual

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

RELATED PRODUCTS

© Honeywell International Inc.