






**Product Family**  
**Titan Fall Limiter**

The Fall Limiter offers 11 ft. working capacity with a quick-activating braking mechanism.



**Product Numbers & Ordering Information**

| Product Numbers  | Details  |
|--|--|
|  TFL-1/11FT | <b>11 ft. of Working Capacity</b><br>Unit Connector: Twist-Lock Carabiner; Lanyard End Connector: Locking Snap Hook                          |
|  TFL-3/11FT | <b>11 ft. of Working Capacity</b><br>Unit Connector: Stainless Steel Swivel Shackle and Carabiner; Lanyard End Connector: Locking Snap Hook  |
|  TFL-6/11FT | <b>11 ft. of Working Capacity</b><br>Unit Connector: Stainless Steel Swivel Shackle and Rebar Hook; Lanyard End Connector: Locking Snap Hook |

**Overview**

**Key Features**

- Requires less fall clearance than shock-absorbing lanyards, making rescue easier and reducing trip hazards
- Increases productivity over a shock-absorbing lanyard by increasing a worker's mobility
- Offers 11 feet (3.3m) of working capacity compared to a standard shock-absorbing lanyard that only provides 6 feet (1.8m) of mobility
- Quick-activating stainless steel braking mechanism arrests free falls
- Compact, lightweight design
- Corrosion-resistant interior components
- No annual factory recertification required
- Visual load indicator

**Hazards**

- Confined Space
- Fall from height

## Regulations

- Meets all applicable OSHA, ANSI and CSA standards

## Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

## Specifications

### Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

## Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

## Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

## Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com