



ReadyRoofer-App-a







**Product Family**  
**Titan ReadyRoofer Fall Protection System**

Roofing bucket kit includes a Titan™ harness, lanyard, roof anchor and rope lifeline.












[Visit MillerFallProtection.com](http://MillerFallProtection.com) >



**Product Numbers & Ordering Information**

Product Numbers	Details
 BRFK100/100FT	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 100-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag
 BRFK100/100FTC	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 100-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag; Canada
 BRFK25/25FT	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 25-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container
 BRFK25/25FTC	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 25-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container; Canada
 BRFK30/30FTC	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 30-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container; Canada
 BRFK50/50FT	<b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 50-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container

## Titan ReadyRoof® Fall Protection System

	BRFK50/50FTC	<p><b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 50-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container; Canada</p>
	BRFK50/XXL/50FT	<p><b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/XXL); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 50-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container</p>
	BRFK75/75FT	<p><b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 75-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag</p>
	BRFK75/75FTC	<p><b>Roof System Kit</b> Full-body harness with mating buckle leg straps (T4000/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 75-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag; Canada</p>
	BRFKT100/100FT	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 100-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag</p>
	BRFKT100/100FTC	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 100-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag; Canada</p>
	BRFKT25/25FT	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 25-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container</p>
	BRFKT25/25FTC	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 25-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container; Canada</p>
	BRFKT50/50FT	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 50-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container</p>
	BRFKT50/50FTC	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab with anti-panic feature (8173); 3-ft. shock-absorbing lanyard (T6111); 50-ft., 5/8-in. dia. rope lifeline (300L-2); waterproof container; Canada</p>
	BRFKT75/75FT	<p><b>Roof System Kit</b> Full-body harness with tongue buckle leg straps (T4500/U); reusable roof anchor; MicroLoc trailing rope grab (8173); 3-ft. shock-absorbing lanyard (T6111); 75-ft., 5/8-in. dia. rope lifeline (300L-2); water-resistant bag</p>



BUCKET/5GAL

**Roof System Kit Accessory**  
5-Gallon Bucket with Lid and Label

## Overview

### Key Features

#### Lightweight, Full-Body Harness

- Fully adjustable, polyester webbing harness for all day comfort and dependability
- Versatile, Reusable Roof Anchor with Attachment D-Ring
- Easily installs on steep-pitched or flat surface roofs with m8 screws included
- Once roofing is complete, remove the reusable roof anchor and store for the next job

#### Compact Trailing Rope Grab

- Durable, corrosion-resistant, stainless steel construction
- Attaches anywhere on the lifeline
- Lightweight, easy-to-use design with hands-free operation offers maximum freedom of movement

#### Shock-Absorbing Lanyard

- 3-foot (.9m) polyester web lanyard with integral shock absorber and two locking snap hooks High-Strength Rope Lifeline
- 5/8-inch (16mm) diameter polypropylene blend rope with loop and locking snap hook
- 9,300 lb. tensile strength, treated to combat ultraviolet rays

#### Water-Proof Container

- Ideal for equipment storage

#### Recommended Industries/Use

- Construction
- Manufacturing

#### Hazards

- Fall from height

#### Regulations

- Meets all applicable OSHA, ANSI and CSA standards

#### Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

## Literature & Documents

#### Miller Temporary Roof Anchors and Kits Manual - US

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Protection\\_Kits/36977/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Protection_Kits/36977/1033.aspx)

I294 - Miller Temporary Roof Anchors and Kits Product Instruction Manual

## Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

## Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

## Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

### RELATED PRODUCTS

© Honeywell International Inc.