







**Product Family**  
**EN T8000 SCBA**

Honeywell T8000 is a Self Contained Breathing Apparatus (SCBA) that is designed to provide a superior and effective safety product for respiratory protection in firefighting and industrial usage that complies with the EN137, Type II Classification. The T8000 SCBA from Honeywell understands a Firefighter's ensemble in high heat conditions, and the level of thermal performance. Firefighters need the finest protection against unforeseen circumstances that are immediately dangerous to life or health.



**Product Numbers & Ordering Information**

Product Numbers	Details
 SCBA-805MLK	<b>T8000 EN Basic, 6.8L 300Bar Composite Cylinder with gauge</b>
 SCBA-805MLK-T	<b>T8000 EN w/ Buddy Breather, 6.8L 300Bar Composite Cylinder with gauge</b>
 SCBA-805MLK-UT	<b>T8000 EN w/ Buddy Breather and UAC, 6.8L 300Bar Composite Cylinder with gauge</b>
 SCBA-05T	<b>Pano Mask Rescue Kit</b>

**Overview**

**Key Features**

- Non-metallic self-extinguishable and ergonomic back-plate
- Perfect weight distribution of the apparatus on hips
- Flexible connector demand Valve with exceptional mobility
- Ergonomically designed and comfortable cushion shoulder harness and Hip Belt
- Reliable reducer system with equalized air flow and isolate second connector outlet
- Technologically advanced high pressure gauge with chest whistle located close to the ear
- Clarity of vision with PANO mask comply with EN 136 standard - Class III

**Recommended Industries/Use**

- Chemical
- Fire Protection
- Government
- Manufacturing
- Mining
- Oil and Gas
- Welding
- Nuclear

**Hazards**

- Airborne Particulates
- Biohazard
- Chemical
- Contamination
- Extreme Environment
- Gas, Vapors, Smoke

**Regulations**

- 

**Historical Brand**

Honeywell

**Specifications**

**Total Weight of the complete apparatus with charge cylinder**

- Approximately 11 kg

**High-pressure pneumatic gauge**

- 0-400 bar, photo-luminescent gauge, rubber protection and integrated alarm whistle

**Alarm activation**

- 55±5 bar

**Alarm volume**

- >90 dBA

**Approve temperatures**

- -30 °C – 60 °C

**Apparatus type-approvals**

- EN 137:2006 Type 2

**Full-face mask type-approval**

- EN 136 Class III

**Literature & Documents**

**T8000 donning poster final**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Respiratory\\_Protection/Self\\_Contained\\_Breathing\\_Apparatus\\_\(SCBA\)/4294997125/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/Self_Contained_Breathing_Apparatus_(SCBA)/4294997125/1033.aspx)

T8000 donning poster final

**T8000 SCBA Fire protector Features and Specifications**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Respiratory\\_Protection/Self\\_Contained\\_Breathing\\_Apparatus\\_\(SCBA\)/4294997126/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/Self_Contained_Breathing_Apparatus_(SCBA)/4294997126/1033.aspx)

T8000 SCBA Fire protector Features and Specifications

**T8000 SCBA USER MANUAL**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Respiratory\\_Protection/Self\\_Contained\\_Breathing\\_Apparatus\\_\(SCBA\)/4294997128/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/Self_Contained_Breathing_Apparatus_(SCBA)/4294997128/1033.aspx)

T8000 SCBA USER MANUAL

**T8000 SCBA technical Datasheet**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Respiratory\\_Protection/Self\\_Contained\\_Breathing\\_Apparatus\\_\(SCBA\)/4294997127/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/Self_Contained_Breathing_Apparatus_(SCBA)/4294997127/1033.aspx)

T8000 SCBA technical Datasheet

