



PRODUCT NUMBER: 1002892

## MH00 - Flexible Rope Anchorage line - 20m

20m, twisted polyamide rope for 14mm /16mm rope grab,  
with counterweight and screwgate karabiner



### Overview

**Reference Number**

1002892

**Product Type**

Fall Protection

**Range**

Anchorage Points

**Brand**

Miller by Honeywell

**Industry**

- Industry
- Building and Construction

**Product Use**

Twisted polyamide rope suitable for 14mm / 16mm rope grabs - 20m Suitable for vertical, horizontal and sloping applications. Supplied with a counterweight and screwgate karabiner ML00

### Features & Benefits

**Feature**

Supplied with a counterweight and screwgate karabiner Complies with EN696

**Benefit**

Reliable and light weight. Suitable for vertical, horizontal and sloping applications.

### Technical Description

#### External

**Rope**

Ø 14 mm polyamid, > 2500 daN

**Connectors**

Galvanised steel

Standard: EN 362

Breaking strength: > 2200 daN

## Dimensions

### Length

20m

### Diameter

14 mm

## Performance

### Breaking Strength

> 22 KN

### Weight (kg)

3.334 kg

### Operating Temperature

-30°C +50°C

### Complementary Information

Counterweigh:

Raw material:

Rubberweight : 0,500 kg

EN 353-2: Guide type fall arresters on a flexible anchorage line Comply with the standard if used with MILLER rope grab only

,

## Additional Information

### User Manual

NT90004209 IND J

### User Information Sheet

User manual

## Packaging

### EAN Code

7312559871455