



sperian\_ref1005317\_photo\_1.jpg

PRODUCT NUMBER: 1005317

## ME82 - Manyard Shock absorbing Lanyard - 1.5m - 2 ML00

Complete 1,5m with 2 galvanised connectors (ML00)



### Overview

#### Reference Number

1005317

#### Product Type

Fall Protection

#### Range

Shock Absorbing Lanyards

#### Brand

Miller by Honeywell

#### Industry

- Industry
- Building and Construction

#### Product Use

**1.5m Shock absorbing Lanyard - complete with 2 galvanised connectors (ML00), with TEFLON finish**

Added elasticity 29.7%

Integrated shock absorber

Highly resistant external webbing, Teflon finish

Warning flag

2 Screw karabiners

Security Clip

### Features & Benefits

#### Feature

A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

#### Benefit

Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or gantries. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

### Technical Description

#### Length

1,5m

**Weight**

0.620 Kg

**Breaking Strength**

> 15 KN

**Operating Temperature**

-30°C to +50°C

**Webbing**

**Webbing Raw Material**

Polyamide

**Webbing Breaking Strength**

> 2500 daN

**Connector**

**Connector Type**

TypeML00

**Connector Raw Material**

Raw MaterialGalvanized steel

**Connector Opening**

Opening18 mm

**Connector Breaking Strength**

Breaking Strength> 2500 daN

**Connector Standard**

StandardEN 362

**Energy Absorber**

**Energy Absorber Raw Material**

Polyester fibers

**Energy Absorber Breaking Strength**

> 500daN

**Complementary Information**

Elasticity : 29.7 % Length Folded : 1.05m Integrated shock absorber Polyester fibers Impact strength reduction: > 500 daN  
External highly resistant webbing: Polyamide webbing 45mm - green Teflon finish Breaking strength: > 2200 daN

**Certifications**

**EU Category PPE**

3

**Quality Assurance**

ISO 9001 / 2000

**EU Certification**

EU Attestation

**Additional Information**

**User Manual**

NT90004208 IND L

**User Information Sheet**

User manual

**Packaging**

**EAN Code**

7312550053171

