



**PRODUCT NUMBER: 6246155**  
**6246155-BACOU TRACK AMG**  
**S3 CI SRC**

- Water resistant oiled full grain leather ankle boot. PU2D outsole injected. SRC certified. 200J Spacium™ toe cap in injected polymer. Flexium™ non-metallic anti-puncture sole. Complies with EN ISO 20345:2011 standard.

## Overview

**Reference Number**

6246155

**Product Type**

Footwear

**Range**

Bacou Original Free

**Brand**

Honeywell

**Brand formerly known as**

BACOU

**Industry**

- Building and Construction
- General Industry
- Logistics
- Maintenance

**Product Use**

- Safety shoes for professional use. Ideal for industry and for work in damp environments

## Features & Benefits

**Feature**

EN ISO 20345:2011 certified. SRC certified.

**Benefit**

Ensures better protection.

**Feature**

Water-resistant oiled full grain leather upper

**Benefit**

Resistant to tearing and spattering of fluids: extended life cycle

**Feature**

Poromax® lining

**Benefit**

Breathable, 3D absorbent & quick-dry interior lining

**Feature**

Flexium™ anti-puncture midsole: non-metallic, made with high tenacity textile fibres

**Benefit**

The midsole is light and flexible. No constraints for the wearer when flexing the foot

**Feature**

Lateral watertight bellows

**Benefit**

Prevents liquid and dust from entering the shoe

**Feature**

Padded ankle collar and tongue

**Benefit**

Adapts to the user's foot shape, ensures comfort when worn for long periods

## Technical Description

**Sizes**

EU: 38 - 47 / UK: 5 - 12

**Table Size**

table\_size\_2749\_id\_2576

**Midsole**

Flexium™ anti-puncture midsole in high tenacity textile.

**Upper**

Water resistant oiled full grain leather upper. Poromax® lining with 3D antibacterial and antimicrobial structure. Lateral watertight bellows. Padded ankle collar and tongue.

**Toe Cap**

200J SPACIUM™ toe cap in injected polymer. Non-metallic: 50% lighter than steel. Extra-wide for greater comfort: suits all foot types. Non magnetic. Thermal insulator. Unalterable.

**Insole**

Dual density PU foam for intensive use. Removeable for easy care. Antibacterial for a longer life span and to prevent odour. Antistatic for optimal efficiency. Comfortable heel pads. Evacuation channels. The Bacou X'Max Black Insole (ref 6000350) can be sold separately. Available from 1 unit (by pair) in an individual packaging

**Outsole**

Dual density polyurethane: PU 2D. Comfort layer of density: 0.5 (guarantees lightness and flexibility, ensures shock absorption and protects against changes in temperature). Outsole layer of density: 1 (resistance to abrasion, fuel oil and grease). High slip resistance due to well defined cleat design, wide, deep and self-cleaning. SRC certified: SRA: on ceramic plates: flat 0,45 (minimum standard: 0,32) heel 0,46 (minimum standard: 0,28) / SRB: on steel floor: flat 0,24 (minimum standard: 0,18) heel 0,24 (minimum standard: 0,13). Energy absorption capacity > 20 joules. Excellent resistance to abrasion: volume loss < 150 mm<sup>3</sup> (with a load of 10 N = 1 kg). Extension before tearing: 650%. Optimised resistance to repeated flexing > 60,000 (standard >30,000). Resistant to acids and alkalis: limited to low concentrations.

**Additional Features**

- CI
- SRC

## Certifications

**EC Category PPE**

2

**Quality Assurance**

ISO 9001 / 2008

**EC Certificate Number**

N°0075/797/161/11/16/1370-EXT 04/11/2016

**EC Attestation**

EC Attestation

**EC Attestation Number**

N°0075/797/161/04/12/0262 ext 34/09/12

**REACH**

<b>EU Regulation 1907/2006 (REACH) Compliance</b>	
The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.	
<b>Product Reference Sold in Europe</b>	<b>Substance &gt; 0.1%</b>
<b>Substance Name</b>	<b>CAS Number</b>
No Substance Content	

**Additional Information****User Manual**

User Instruction EN ISO 20345 2011-Footwear-Honeywell-032012

**Maintenance****Life Cycle**

- We advise that the footwear should be used in the limit of 3 years following the manufacturing date, which figures on the footwear.
- After this time limit, certain factors such as: exposure to sunlight, hydrometry, temperature changes, could cause a modification in the structure of the material, which would no longer maintain the same performance levels with regards to the requirements defined in the European Directive 89.686 CEE.

**Storage Information**

- Footwear should be stored in their original packaging, kept in a controlled stock area, not subject to rapid changes in temperature or humidity levels.

**Care Instructions**

- After use leave your footwear to dry in an aired place away from heat. Remove any excess dust or dirt with a brush. Remove any marks using a damp cloth and soap if necessary.
- Finally polish any grain or pigmented leathers using a commercially available shoe care product.