

Miller® Black Rhino™ Fall Arrestors

Product description

Miller® Black Rhino fall arrestors are an ultra small and light-weight cable lifeline.

Designed with stainless steel cable, the Black Rhino fall arrestor was developed to endure the daily rigors of harsh environments such as concrete construction, welding, steel erection, food processing and warehousing applications. The 2.7m of working capacity offers greater mobility and arrests a fall within centimeters, minimising the risk to the employee in the event of a fall.

A shorter arrest distance usually positions the user where they can be quickly rescued. This light-weight unit also features an integral load indicator which shows when the unit must be removed from service. It has corrosion resistant stainless steel and aluminium components.

FEATURES

- Quick activating high strength stainless steel braking system.
- Integral load indicator shows if a fall has been taken.
- Integral internal shock absorber limits fall forces to under 4kN.
- Corrosion resistant stainless steel and aluminium components.
- Variety of anchorage connectors available including a swivel hook, or triple action karabiner terminations.
- No annual recertification required.

APPLICATIONS

- Concrete Construction
- Welding at height
- Steel erection
- Food Processing industries
- Warehousing applications

Ordering Details

PART NO.	DESCRIPTION	LENGTH	TERMINATIONS	MIN QTY	CAT	PACKAGE DIMENSIONS	WEIGHT	BARCODE
CFL2.7M-7/-AUS	Black Rhino™ fall arrestor	2.7m	Karabiner/19mm swivel	1	A	240 x 170 x 100	2.4kg	512230121716
CFL2.7M-8/-AUS	Black Rhino™ fall arrestor	2.7m	Triple acting karabiner e/end	1	A	240 x 170 x 100	2.2kg	612230121723

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
New Zealand 0800 322 200
www.honeywellsafety.com

Doc | Rev | 09/16
© 2016 Honeywell Safety Products Australia Pty Ltd



Technical Information

Max working load:	140kg
Cover:	Impact resistant thermoplastic over aluminium
Housing:	Aluminium
Hub:	Zinc
Breaking Mechanism:	Stainless Steel
Cable:	Stainless Steel
Hook:	Zinc-plated with 19mm opening.

Standards

Fully compliant to AS/NZS 1891.3 as a type 2 fall arrest device.