

Miller® Falcon™ Fall Arrestor Range

Product description

Nearly indestructible, the high impact-resistant nylon housing withstands the harsh rigors of the toughest applications. These light, most rugged line of composite fall arrestors are designed with smooth, round edges to increase durability.

FEATURES

- Corrosion-resistant stainless steel and aluminium internal components extend service life and reduce replacement costs.
- Lightest composite unit on the market – easy to handle and transport to and from job sites.
- Unique side payout design reduces wear on the entry guide bushing and cable for smooth operation with less drag.
- Smooth, quiet operation; engineered spring retraction tension designed not to pull or drag on a worker to improve productivity and reduce fatigue.
- Built-in, ergonomically-designed molded handle on the 15m and 20m units makes the units easier to install.
- Dual swivels (unit top and snap hook) included on all models to minimise lifeline from twisting during use.
- New and improved load indicator on the snap hook identifies when the unit needs to be removed from service.
- No annual factory recertification required – lowers cost of ownership and increases productivity.
- Return to manufacturer after five years for recertification and annually thereafter.

APPLICATIONS

- Construction
- Maintenance
- Elevated Work Platforms
- Warehousing
- Steel Erection
- Concrete construction



Falcon 6m, 10m, 15m & 20m stainless steel units



Falcon 6m, 10m, 15m & 20m galvanized units



Falcon 6m webbing

Technical Information

Housing:	High impact nylon
Ferrules:	Fasteners & Top Swivel: Stainless Steel
Cable:	Aluminium or Copper
Snaphook:	Galvanized or Stainless Steel
Brake Pawls:	Drop Forged Steel
Drum:	Bronze
Frame Plates:	Aluminium
Power Spring & Main-shaft:	Aluminium or Stainless Steel
	Stainless Steel
Max Working Load:	136 kg
Ultimate Tensile Strength:	16.01kN
Free Fall Distance:	Max. 609.6mm
Deceleration Distance:	Max – 1.06m
Arresting Force:	4kN (approx)

Standards

Fully compliant to AS/NZS 1891.3 as a Type 2 fall arrest device

Ordering Details

PART NO.	DESCRIPTION	LENGTH	MATERIAL	MIN QTY	CAT	PACKAGE DIMENSIONS	WEIGHT	BARCODE
1011728	Falcon	6m	Galvanised Cable	1	A	420 x 260 x 130	4kg	9333633007957
1011742	Falcon	10m	Galvanised Cable	1	A	420 x 260 x 130	4.8kg	9333633007971
1011746	Falcon	15m	Galvanised Cable	1	A	420 x 260 x 130	6.7kg	9333633007995
1011750	Falcon	20m	Galvanised cable	1	A	420 x 260 x 130	7.7kg	9333633008015
1028680	Falcon	6m	Stainless steel cable	1	A	420 x 260 x 130	4kg	3660681034311
1028681	Falcon	10m	Stainless steel cable	1	A	420 x 260 x 130	4.8kg	3660681031655
1028682	Falcon	15m	Stainless steel cable	1	A	420 x 260 x 130	6.7kg	3660681044259
1028683	Falcon	20m	Stainless steel cable	1	A	420 x 260 x 130	7.7kg	3660681044242
1016794	Falcon	6m	Webbing with aluminium scaffold hook and 18mm screw-gate karabiner	1	A	270 x 190 x 130	1.98kg	3660681041302
1016796	Falcon	6m	Webbing with aluminium screw-gate karabiner and 22mm snap hook	1	A	270 x 190 x 130	1.58kg	3660681041326

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
 New Zealand 0800 322 200
www.honeywellsafety.com