

SPERIAN POWERCOAT® - CHEMICAL GLOVES



PRODUCT INFORMATION

Sizes Available	Part #	UPC		
Medium	610-M	801462140392		
Large	610-L	801462140385		
XLarge	610-XL	801462140415		
XXLarge	610-XXL	801462140422		
Polymer and Color:	Double dipped PVC - Orange		Liner:	100% Cotton Seamless Knit
Mil Thickness:	NA		Length:	10 inches
Cuff Style:	Pinked		Finish:	Rough
Disposable Box Qty:	72 pairs		Country of Origin:	Pakistan

PRODUCT FEATURES

- PVC is effective for oil resistance
- PVC is the most flexible and comfortable of all polymers
- Durable double dipped coating
- Cotton knit liner helps to wick away hand moisture

TESTING INFORMATION

Chemical	Mean Thickness	Breakthrough Time (minutes)	Performance Level (Based on lowest break-through time)
Methanol (A)	1.4mm	38	Level 2
n-Heptane (J)	1.4mm	39	Level 2
96% Sulfuric Acid (I)	1.4mm	47	Level 2

	Test Method	Level	Test Result
Abrasion Resistance:	ASTM 3389-05	not tested	≥ cycles
	EN388	Level 4	≥ 8,000 cycles
Cut Resistance:	ASTM F1790-97	not tested	≥ grams
	EN388	Level 1	≥ 1.2 grams
Tear Resistance:	EN388	Level 2	≥ 25 Newtons
Puncture Resistance:	EN388	Level 1	≥ 20 Newtons

CARE INSTRUCTIONS

PVC gloves should be kept in a closed container, away from sunlight, artificial light, humidity and stored at temperatures between 40° F and 95° F. Proper storage and maintenance should preserve products for the full shelf life of approximately 2.5 years. Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

⚠️ WARNINGS

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Hand protection with a Perfect Fit

Sperian Protection Americas, Inc. | 900 Douglas Pike, Smithfield, RI 02917-1874 | tel: 1.800.430.5490 | fax: 1.800.322.1330