

SPERIAN POWERCOAT® - CHEMICAL GLOVES

PRODUCT INFORMATION

Sizes Available	Part #	UPC
Medium	460-M	801462129205
Large	460-L	801462129199
XLarge	460-XL	801462129212



Polymer and Color:	Double dipped PVC - Orange	Liner:	Acrylic/Wool Thermal Fleece
Mil Thickness:	NA	Length:	12 inches
Cuff Style:	Over-edged	Finish:	Rough
Disposable Box Qty:	72 Pairs	Country of Origin:	Pakistan

PRODUCT FEATURES

- PVC is effective for oil resistance
- PVC is the most flexible and comfortable of all polymers
- Durable double dipped coating
- Thermal fleece liner for added warmth and cushion comfort

TESTING INFORMATION

Chemical	Mean Thickness	Breakthrough Time (minutes)	Performance Level (Based on lowest break-through time)	Cold Resistance (In accordance with EN511)	Performance Level
Methanol (A)	3.5mm	38	Level 2	Convective Cold	Level 1
n-Heptane (J)	3.5mm	39	Level 2	Contact Cold	Level 2
96% Sulphuric Acid (L)	3.5mm	47	Level 2	Water Impermeability	Level 1

	Test Method	Level	Test Result
Abrasion Resistance:	ASTM 3389-05	not tested	≥ cycles
	EN388	Level 4	≥ 8,000 cycles
Cut Resistance:	ASTM F1790-97	not tested	≥ grams
	EN388	Level 1	≥ 1.2 grams
Tear Resistance:	EN388	Level 2	≥ 25 Newtons
Puncture Resistance:	EN388	Level 1	≥ 20 Newtons

CARE INSTRUCTIONS

PVC gloves should be kept in a closed container, away from sunlight, artificial light, humidity and stored at temperatures between 40° F and 95° F. Proper storage and maintenance should preserve products for the full shelf life of approximately 2.5 years. Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

⚠️ WARNINGS

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Hand protection with a Perfect Fit

Sperian Protection Americas, Inc. | 900 Douglas Pike, Smithfield, RI 02917-1874 | tel: 1.800.430.5490 | fax: 1.800.322.1330