

SPERIAN POWERCOAT® - CHEMICAL GLOVES



PRODUCT INFORMATION

Sizes Available	Part #	UPC		
Medium	650-M	801462140705		
Large	650-L	801462140682		
XLarge	650-XL	801462140729		
XXLarge	650-XXL	801462140743		
Polymer and Color:	Triple dipped PVC - Blue		Liner:	100% Cotton seamless knit
Mil Thickness:	NA		Length:	10 inches
Cuff Style:	Pinked		Finish:	Rough
Disposable Box Qty:	72 pairs		Country of Origin:	Pakistan

PRODUCT FEATURES

- PVC is effective for oil resistance
- PVC is the most flexible and comfortable of all polymers
- Durable double dipped coating
- Cotton knit liner helps to wick away hand moisture

TESTING INFORMATION

Chemical	Mean Thickness	Breakthrough Time (minutes)	Performance Level (Based on lowest break-through time)
n-Heptane (J)	1.5mm	38	Level 2
40% Sodium Hydroxide (K)	1.5mm	>480	Level 6
96% Sulfuric Acid (I)	1.5mm	160	Level 4

	Test Method	Level	Test Result
Abrasion Resistance:	ASTM 3389-05	not tested	≥ cycles
	EN388	Level 4	≥ 8,000 cycles
Cut Resistance:	ASTM F1790-97	not tested	≥ grams
	EN388	Level 1	≥ 1.2 grams
Tear Resistance:	EN388	Level 2	≥ 25 Newtons
Puncture Resistance:	EN388	Level 1	≥ 20 Newtons

CARE INSTRUCTIONS

PVC gloves should be kept in a closed container, away from sunlight, artificial light, humidity and stored at temperatures between 40° F and 95° F. Proper storage and maintenance should preserve products for the full shelf life of approximately 2.5 years. Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

⚠️ WARNINGS

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Hand protection with a Perfect Fit

Sperian Protection Americas, Inc. | 900 Douglas Pike, Smithfield, RI 02917-1874 | tel: 1.800.430.5490 | fax: 1.800.322.1330