

▶ ▶ ▶ AIRSoft® MULTIPLE USE EARPLUG

PRODUCT INFORMATION

Advanced Air Pocket Design utilising advances in acoustical engineering, AirSoft's new internal fins create an interlocking, noise blocking barrier within the air pocket, providing dependable attenuation for all wearers upon proper insertion. AirSoft also attenuates better across the entire frequency range, offering the highest in multiple-use protection with an SLC₈₀ 26dB Class 5.

Optimised for exceptional in-ear comfort, AirSoft's new four flange profile creates a better seal in the ear canal, delivering optimal protection and increased comfort for long-term wear. At the same time, AirSoft's firm stem and tapered shape facilitates easy insertion and removal, and allows the earplug to sit comfortably in the ear canal.

PRODUCT FEATURES

- ⇒ Optimised for Superior Fit, Comfort and Protection.
- ⇒ Easier Handling – Firm stem facilitates proper insertion and removal.
- ⇒ Improved Comfort – Soft rounded flanges, baffled air pocket feels more comfortable in your ear.
- ⇒ SLC₈₀ 26dB – Highest attenuation in multiple-use earplugs, ideal for medium and high levels of hazardous noise exposure.
- ⇒ Blue Color – Contrasting color ideal for process industries that require visual inspection.
- ⇒ Available corded or uncorded with flip top box, of safety impact case packaging options.

APPLICATIONS

- ⇒ Any noise environment 105dB to less than 110dB



DPAS-30W

AS-30R
DPAS-30R

AS-1

TECHNICAL INFORMATION

| | |
|----------------|-----------------------------------------------|
| Material: | Thermoplastic Elastomer |
| Diameter: | 12.19mm |
| Length: | 31.55mm |
| Cord Length: | 711.2mm - |
| Cord Material: | PVC (red), Nylon (white) |
| Weight: | 0.91g |
| Colour: | Blue |
| Storage Case: | Polybag or PVC or Impact case - polypropylene |
| Temperature: | -26°C to +60°C |

STANDARDS

- ⇒ Approved to AS/NZS 1270:2002
License number 1579
- ⇒ SLC₈₀ 26dB Class 5

| Frequency | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|------------------|------|------|------|------|------|------|------|
| Mean Value dB | 33.0 | 32.6 | 32.3 | 31.9 | 33.9 | 35.6 | 40.6 |
| Std Deviation dB | 8.1 | 9.3 | 10.2 | 9.3 | 6.5 | 8.4 | 6.1 |
| Mean-Std Dev dB | 25.0 | 23.3 | 22.1 | 22.6 | 27.4 | 27.3 | 34.5 |

ORDERING INFORMATION

| Part Number | Description | Pairs Per Box | Min order (box) | Box dimensions L x H x D (mm) | Box Weight | Case Dimensions L x H x D (mm) | Case Weight | Bar code |
|-------------|---------------------------|---------------|-----------------|-------------------------------|------------|--------------------------------|-------------|--------------|
| AS-1 | Uncorded, Reuseable Case | 50 | 1 | 203 x 197 x 129 | 727g | 650 x 205 x 426 | 7.27kg | 033552000242 |
| AS-30R | Polycord, Reuseable Case | 50 | 1 | 203 x 197 x 129 | 818g | 650 x 205 x 426 | 8.18kg | 033552000372 |
| DPAS-30R | Red Vinyl Cord, polybag | 100 | 1 | 203 x 197 x 129 | 725g | 650 x 205 x 426 | 7.25kg | 033552000969 |
| DPAS-30W | White Nylon Cord, polybag | 100 | 1 | 203 x 197 x 129 | 689g | 650 x 205 x 426 | 6.89kg | 033552001034 |

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.