

Fenzy Xpro

Product description

Developed and designed in collaboration with fire-fighting professionals, the Fenzy X-Pro utilises the latest technologies to create an SCBA which is resistant to extreme temperatures.

FEATURES

- Robust Swivel Adjustment on the back-plate allows the SCBA to follow all movements of the top half of the wearers back
- Height adjustment device on backplate to allow the SCBA to fit many different body shapes and sizes.
- Articulated waistbelt follows the hip movements of the wearer in all positions
- Movable foot protects the cylinder valve and reducer
- Side Carry handles for ease of carrying when not wearing the SCBA
- SXPRO first breath demand valve
- Quick Fix system transforms from a single to a twin cylinder set up

APPLICATIONS

- The XPro is designed for use in Fire Fighting and applications requiring extreme heat resistance.



Technical Details

Pressure:	200 or 300 bar
Outlet pressure of the HP reducer:	7 bar
Maximum Flow (lpm):	1000
Activation of the warning whistle:	55 bar
Power of the pressure gauge whistle:	>95 dBA
Frequency of the pressure gauge whistle:	>3000 Hz
Operating Temperature:	-10°C - +60°C
OptiPro Mask Visor:	Polycarbonate

Standards

Certified to AS/NZS 1716:2003 Licence No: 21516

Ordering Details

PART NO.	DESCRIPTION	MIN QTY	BOX QTY	CASE QTY	WEIGHT
1823382	Fenzy Xpro with Optipro full face mask	1	1	1	3.9Kg
1715029	Fenzy OptiPro full face mask	1	1	1	900g

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
 New Zealand 0800 322 200
www.honeywellsafety.com