

EC TYPE-EXAMINATION CERTIFICATE :1286

Product description:-

Ear-muffs

Product identification:-

Bilsom Leightning L2Fs

Manufactured by:-

Bacou-Dalloz AB
Dungattan 2
260 50 Billesholm
Sweden

When assessed and examined against harmonised standard EN352-1:2002 is found to be in conformity with Council Directive 89/686/EEC, and associated amendments, relating to personal protective equipment .

Signed

Date: 17th December 2004

K J Warren, Manager, Certification Services

For and on behalf of INSPEC International Ltd. (Notified Body No: 0194)

For terms and conditions of issue, see page 2

certificate invalid
if not embossed

Terms and Conditions associated with INSPEC
EC Type-Examination Certificate No: 1286

Reference Documents:-

- | | | | |
|------|--------------------------|---|--|
| i) | Test Reports | - | INSPEC 04.11.99 |
| ii) | Technical File | - | INSPEC ref. TF/1286 |
| iii) | Test and Inspection Plan | - | CE Product Certification, Test and Inspection Plan |

Conditions attached to the issue of this certificate:

- i) Marking and instructions have been assessed in the English language only. It is the Manufacturers/Authorised Representatives responsibility to obtain and supply language versions acceptable to the country where the product is to be sold.
- ii) Any changes to the product, technical file or quality manual/quality plan shall be immediately notified to INSPEC.
- iii) The Manufacturer/Authorised Representative shall comply at all times with INSPEC's Regulations governing CE Product Certification.
- iv) This Certificate remains the property of INSPEC and may be withdrawn if any of the conditions attached to its issue are not complied with.

CERTIFICATION SCHEDULE

COMPANY: Bacou-Dalloz AB

CERTIFICATE NO: EC1286

SCHEDULE NO: TWO

DATE: 12th September 2005


Model: Bilsom Leightning L2Fs, Bilsom Leightning L2Fs HI-VISIBILITY

Description: Over the head ear-muff

Size Range: S / M / L

Attenuation Data

Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
Mean att. (dB)	19.6	21.1	25.8	30.5	35.7	33.6	37.8	37.3
Std. Dev. (dB)	4.3	3.6	2.1	2.6	3.0	3.1	2.7	3.6
APV (dB)	15.3	17.5	23.7	27.9	32.7	30.5	35.1	33.7
	H = 32dB		M = 30dB		L = 24dB		SNR = 32dB	

Signed for and on behalf of INSPEC.....

Kevin Warren, Manager, Certification Services